

The latex-lab-unicode-math code*

L^AT_EX Project

May 19, 2025

Abstract

Contents

1	Introduction	1
2	The Implementation	1
2.1	File declaration	1
2.2	Sockets	1
2.3	Delimiters	2
2.4	varlim-commands	2
2.5	Roots	2
2.6	Fractions	3
	Index	3

1 Introduction

This file implements temporary adaptations to the unicode-math package needed for the tagging project.

2 The Implementation

1 `<@@=math>`

2 `<*kernel>`

2.1 File declaration

```
3 \ProvidesExplFile
4 {latex-lab-unicode-math.ltx}
5 {2025-02-26}
6 {0.1b}
7 {unicode-math adaptations}
```

*

2.2 Sockets

Unicode glyphs like a root sign should be marked as artifacts to avoid duplication in derivation if mathml structure elements are used. This is done with a luamml socket.

```

8 \str_if_exist:cF { l__socket_tagsupport/math/luamml/artifact_plug_str }
9 {
10   \NewTaggingSocket{math/luamml/artifact}{0}
11 }

```

2.3 Delimiters

Extensible delimiters set with `\bigl`, `\Bigl`, etc. use boxes in their definitions. This gives wrong structure elements if used with luamml. We therefore redefine the internal `amsmath` command to make use of the `luatex` primitive.

```

\bigg@
12 \def\bigg@#1#2
13 {{\ensuremath {\Uvextensible height~#1 \big@size axis-exact~#2}}}

```

(End of definition for `\bigg@`. This function is documented on page ??.)

2.4 varlim-commands

The commands `\varinjlim`, `\varliminf`, `\varprojlim` and `\varlimsup` use boxes that confuse luamml. We redefine them to use `luatex` primitives. This slightly changes the look!

```

14 \protected\def\varinjlim
15 {{\Udelimiterunder 0 "2192 {\qopname\relax o{\luamml_ignore:\mathstrut lim}}}}
16 \protected\def\varprojlim
17 {{\Udelimiterunder 0 "2190 {\qopname\relax o{\luamml_ignore:\mathstrut lim}}}}
18 \protected\def\varlimsup
19 {{\overline{\qopname\relax o{\luamml_ignore:\mathstrut lim}}}}
20 \protected\def\varliminf
21 {{\underline{\qopname\relax o{lim}}}}

```

2.5 Roots

Roots have two problems in tagging: At first, if mathml structure elements are used, the root symbol is given twice: as Unicode char and through the `msqrt` or `mroot` mathml structure element. In derivation this leads to duplications. The glyph should be tagged as artifact in this case. At second, in some cases complicated box constructions instead of the `luatex` primitives are used which leads to wrong tagging. We redefine `\sqrtsign` and add the artifact socket for the first problem.

TODO: A root with empty argument should be tagged differently.

```

22 \AtBeginDocument
23 {
24   \cs_gset_protected_nopar:Npn \sqrtsign
25   {
26     \tag_socket_use:n {math/luamml/artifact}
27     \tex_Uradical:D \symoperators "0221A\scan_stop:
28   }
29 }

```

TODO: Tagging of `\sqrt[\leftroot{-2}\uproot{2}\beta]{y}` is currently incorrect, but setting `\Umathradicaldegreeraise` and `\Umathradicaldegreeafter` does not work, so another solution must be found (or a warning must be issued).

```

30 \cs_set_nopar:Npn \plainroot@ #1 \of #2
31 {
32   \bool_if:nTF
33   {
34     \__um_int_if_zero_p:n \uproot@ && \__um_int_if_zero_p:n \leftroot@
35   }
36   {
37     \tag_socket_use:n {math/luamml/artifact}
38     \Uroot \c__um_radical_sqrt_tl { #1 } { #2 }
39   }
40   {
41     \hbox_set:Nn \rootbox
42     {
43       \c_math_toggle_token \m@th
44       \scriptscriptstyle { #1 }
45       \c_math_toggle_token
46     }
47     \mathchoice
48     { \r@@t \displaystyle { #2 } }
49     { \r@@t \textstyle { #2 } }
50     { \r@@t \scriptstyle { #2 } }
51     { \r@@t \scriptscriptstyle { #2 } }
52   }
53   \c_group_end_token
54 }

```

2.6 Fractions

Similar to roots in fractions the rule must be marked as artifact.

```

55 \DeclareRobustCommand {\frac}[2]
56 {{\tag_socket_use:n{math/luamml/artifact}\Ustack{\begingroup#1\endgroup\@@over#2}}}
57 </kernel>

```

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

A		P	
<code>\AtBeginDocument</code>	22	<code>\protected</code>	14, 16, 18, 20
B		<code>\ProvidesExplFile</code>	3
<code>\begingroup</code>	56	Q	
<code>\Bigl</code>	2	<code>\qopname</code>	15, 17, 19, 21
<code>\bigl</code>	2	R	
bool commands:		<code>\relax</code>	15, 17, 19, 21
<code>\bool_if:nTF</code>	32	<code>\rootbox</code>	41
C		S	
cs commands:		scan commands:	
<code>\cs_gset_protected_nopar:Npn</code>	24	<code>\scan_stop:</code>	27
<code>\cs_set_nopar:Npn</code>	30	<code>\scriptscriptstyle</code>	44, 51
D		<code>\scriptstyle</code>	50
<code>\DeclareRobustCommand</code>	55	<code>\sqrtsign</code>	2, 24
<code>\def</code>	12, 14, 16, 18, 20	str commands:	
<code>\displaystyle</code>	48	<code>\str_if_exist:NTF</code>	8
E		<code>\symoperators</code>	27
<code>\endgroup</code>	56	T	
<code>\ensuremath</code>	13	tag commands:	
F		<code>\tag_socket_use:n</code>	26, 37, 56
<code>\frac</code>	55	TeX and L ^A T _E X 2 _ε commands:	
G		<code>\@@over</code>	56
group commands:		<code>\bBigg@</code>	12
<code>\c_group_end_token</code>	53	<code>\big@size</code>	13
H		<code>\leftroot@</code>	34
hbox commands:		<code>\m@th</code>	43
<code>\hbox_set:Nn</code>	41	<code>\plainroot@</code>	30
L		<code>\r@t</code>	48, 49, 50, 51
luamml commands:		<code>\uproot@</code>	34
<code>\luamml_ignore:</code>	15, 17, 19	tex commands:	
M		<code>\tex_Uradical:D</code>	27
<code>\mathchoice</code>	47	<code>\textstyle</code>	49
<code>\mathstrut</code>	15, 17, 19	token commands:	
N		<code>\c_math_toggle_token</code>	43, 45
<code>\NewTaggingSocket</code>	10	U	
O		<code>\Udelimiterunder</code>	15, 17
<code>\of</code>	30	um internal commands:	
<code>\overline</code>	19	<code>__um_int_if_zero_p:n</code>	34
		<code>\c_um_radical_sqrt_tl</code>	38
		<code>\Umathradicaldegreeafter</code>	2
		<code>\Umathradicaldegreeraise</code>	2
		<code>\underline</code>	21
		<code>\Uroot</code>	38
		<code>\Ustack</code>	56
		<code>\Uvextensible</code>	13

	V		<code>\varlimisup</code>	2
<code>\varinjlim</code>	2, 14	<code>\varlimsup</code>	18	
<code>\varliminf</code>	2, 20	<code>\varprojlim</code>	2, 16	